

RECEIVED
CENTRAL FAX CENTER
JUL 07 2006

Listing of Claims:

No amendments to the claims are being presented at this time. This listing of claims is provided merely for convenience, and will replace all prior versions and listings of claims in the application:

1. (Previously presented) A drill sharpener comprising a housing which encloses a rotatable grinding wheel assembly, the housing having a point-splitting port to facilitate a point-splitting operation upon a multi-flute drill bit to remove material between said flutes, the port comprising a guide feature that maintains a longitudinal length of the bit along a predetermined axial line and at a predetermined angular orientation with respect to said line as said material is removed by the grinding wheel assembly, and wherein the point-splitting operation is carried out by inserting the bit into the port and using the guide feature to maintain the bit in a first orientation while removing a first portion of said material from the bit, removing the bit from the port, and reinserting the bit into the port and using the guide feature to maintain the bit in a second orientation that is 180 degrees opposite the first orientation with respect to the axial line while removing a second portion of said material from the bit.

2. (Previously presented) A drill sharpener as recited in claim 1, wherein said point-splitting port has an opening slightly larger than a barrel of a chuck to be inserted therein, the chuck adapted to hold said bit during said point-splitting operation, and wherein the guide feature cooperates with a surface of the chuck to maintain the bit along said predetermined axial line and at said predetermined angular orientation.

3. (Previously presented) A drill sharpener as recited in claim 2, wherein the port further comprises a generally cylindrical wall of the housing and wherein the guide feature comprises a resilient portion of said generally cylindrical wall and a flange protruding radially inwardly from said resilient portion of said wall.

4. (Previously presented) A drill sharpener as recited in claim 3, wherein said resilient portion of said wall comprises a tongue element formed in said wall and attached to said wall at one end thereof.

5. (Previously presented) A drill sharpener as recited in claim 1, wherein the port further comprises a stop feature that limits further advancement of the bit along the predetermined axial line to limit the amount of said material removed from said bit.

6. (Previously presented) A drill sharpener as recited in claim 1, further comprising a chuck adapted to support the bit during insertion of the bit into the port, the chuck comprising an outer surface with a recess extending therein, the recess configured to engage the guide feature of the port.

7. (Previously presented) A drill sharpener comprising a housing which encloses a grinding wheel assembly and a chuck adapted to securely retain a multi-flute drill bit, the housing comprising a sharpening port adapted to receive the chuck to present said drill bit to the grinding wheel assembly to sharpen said flutes, the housing further comprising a point-splitting port adapted to receive the chuck to present said drill bit to the grinding

wheel assembly to remove material between said flutes, wherein the point-splitting port comprises a guide feature that maintains a longitudinal length of the bit along a predetermined axial line and at a constant angular orientation with respect to said line prior to and during the point-splitting operation.

8. (Previously presented) A drill sharpener as recited in claim 7, wherein the point-splitting port has an opening slightly larger than a barrel of the chuck, and wherein the guide feature cooperates with a surface of the chuck to maintain the bit along said predetermined axial line and at said predetermined angular orientation during the point-splitting operation.

9. (Previously presented) A drill sharpener as recited in claim 7, wherein the point-splitting port further comprises a generally cylindrical wall of the housing and wherein the guide feature comprises a resilient portion of said generally cylindrical wall and a flange protruding radially inwardly from said resilient portion of said wall.

10. (Previously presented) A drill sharpener as recited in claim 9, wherein said resilient portion comprises a tongue element formed in said wall and attached to said wall at one end thereof.

11. (Previously presented) A drill sharpener as recited in claim 7, wherein the point-splitting port further comprises a stop feature that limits further advancement of the bit

along the predetermined axial line to limit the amount of said material removed from said bit.

12. (Previously presented) A drill sharpener as recited in claim 7, wherein the housing further comprises a sharpening port adapted to receive the chuck to present said drill bit to the grinding wheel assembly to sharpen said flutes, wherein the drill sharpener further comprises a debris collector to collect debris from the grinding wheel assembly, and wherein the collector is adapted to be removeably coupled to either one of said ports while the chuck is inserted into the remaining one of said ports.

13. (Previously presented) A drill sharpener comprising:

a chuck adapted to securely retain a multi-flute drill bit;

a housing which encloses a grinding wheel assembly, the housing comprising a sharpening port adapted to receive the chuck to present said drill bit to the grinding wheel assembly to sharpen said flutes and a point-splitting port adapted to receive the chuck to present said drill bit to the grinding wheel assembly to remove material between said flutes; and

a debris collector to collect debris from the grinding wheel assembly, wherein the collector is adapted to be removeably coupled to either one of said ports while the chuck is inserted into the remaining one of said ports, and wherein the debris collector is further adapted to be connected to a vacuum hose.

14. (Previously presented) A drill sharpener as recited in claim 13, wherein said debris collector comprises a hollow body and a cap secured at an end of the body opposite an end that interfaces with said ports.

15. (Previously presented) A drill sharpener as recited in claim 14, wherein said cap is vented to permit gas to flow therethrough while substantially preventing solid particles of selected size from exiting said cap.

16. (Previously presented) A drill sharpener as recited in claim 14, wherein said cap is removable from said body.

17. (Previously presented) A drill sharpener as recited in claim 13, wherein the point-splitting port is configured to facilitate a point-splitting operation upon the bit to remove material between said flutes, the port comprising a guide feature that maintains a longitudinal length of the bit along a predetermined axial line and at a predetermined angular orientation with respect to said line as said material is removed by the grinding wheel assembly.

18. (Previously presented) A drill sharpener as recited in claim 13, wherein the debris collector forms an elbow so that the collector can be canted downwardly when inserted into said ports.